

## ESPRIMO Mobile V5505

Issue February 2008

Pages 3

The ESPRIMO Mobile V5505 is a versatile all-round notebook, equally suitable for occasional or professional users, and heavy-duty operation by mobile field sales people.

This professional notebook features a superb 15.4-inch WXGA display, an ergonomic keyboard and a built-in super multi DVD writer drive. LAN are integrated for easier connection, courtesy of the latest Intel® Centrino® Duo Mobile Technology based on Intel® 965GM chipset. It has great connections; four USB ports and an integrated 3in1 Card Reader. Connect to printers, scanners, cameras or any other accessory.

### Elegance

Designed for the most demanding mobile users, ESPRIMO Mobile is the perfect synthesis of form, function and style.

- Power-saving Intel® Centrino® Duo Mobile for long independent working
- Increased productivity due to latest Intel® 965GM chipset which supports latest technology standards: DDR2 memory, PCI Express and S-ATA

### Ergonomics

- Enjoy the viewing quality of brilliant 15.4-inch WXGA TFT display
- Convenient working with full sized keyboard

### Connectivity

- Ideal connectivity through WLAN. Antennas are integrated for best signal reception.
- Variety of interfaces for best connection to the peripherals

### Reliability

- Germany's quality standard
- Award-winning best-in-class manufacturing
- Mechanical and function stability through extensive quality tests



System	ESPRIMO Mobile V5505
<b>Processor</b> Intel® Core™2 Duo Processor Second level cache Front side bus (FSB) Intel® Core™2 Duo Processor Second level cache Front side bus (FSB)	Up to T7500 (2.2 GHz) 4 MB 800 MHz Up to T8100 (2.1 GHz) 3 MB 800 MHz
<b>Chipset</b> Northbridge Southbridge	Intel® 965GM ICH 8-M
<b>Memory</b> DIMM slots (667 MHz) DDR2-667 SDRAM	2 up to 4 GB supported
<b>BIOS</b> BIOS Flash EPROM	Phoenix First BIOS
<b>Interfaces</b> Express Card slot (34/54mm) 3in1 Card Reader (SD, MMC and memory stick) USB 2.0 S-Video out (TV-out) VGA Modem RJ 11 LAN RJ-45 Audio-in (line-in / microphone) Audio-out (line-out / headphone) DC-in Kensington Lock	1 1 4 1 1 Optional 1 1 1 1 1
<b>Modem on board</b> 56K V.92 modem MDC1.5	Optional
<b>Intel® Turbo Memory</b>	Optional
<b>LAN on board</b> built-in 10/100/1000 Mbps (Realtek 8111B-GR)	x
<b>Wireless Technologies (WLAN)</b> Import and usage according to country-specific regulations. Intel® PRO/Wireless 3945 ABG Intel® PRO/Wireless 4965AGN	- Optional Optional
<b>Bluetooth</b> Bluetooth V2.0	Optional
<b>Audio</b> Stereo speakers Internal microphone	Conexant CX20549 x x
<b>Keyboard and pointing device</b> Keyboard Touchpad Status LED	85 keys, 19mm pitch 2.5mm key stroke with two mouse buttons x
<b>Graphics</b> Intel® GMA X3100 (shared memory up to 384 MB)* Direct X9 Pixelshader 2.0 DualView * depending on system memory	x x x x
<b>Display</b> 15.4-inch TFT WXGA / 1280 x 800 pixel non glare (glare optiona ) Max. resolution for external displays	x Up to 1920 x 1440 / true color / 60 Hz
<b>Hard disk drives (internal) *</b> S.M.A.R.T. 80 GB S-ATA 150 (5400 rpm) 120 GB S-ATA 150 (5400 rpm) 160 GB S-ATA 150 (5400rpm) 250 GB S-ATA 150 (5400rpm) 320 GB S-ATA 150 (5400rpm) * 1 Gbyte equals one billion bytes, when referring to hard disk drive capacity; accessible capacity may vary, also depending on used software and tool.	x x x x x x
<b>Fixed drives</b> Super Multi DVD writer (incl DVD RAM, 8x double layer support) More information in specific Data Sheet: <a href="http://www.fujitsu-siemens.com/optical_drives/">http://www.fujitsu-siemens.com/optical_drives/</a>	x
<b>Manageability</b> Please refer to <a href="http://www.fujitsu-siemens.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html">http://www.fujitsu-siemens.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html</a> <b>Supported Standard</b> WMI / CIM / WBEM PXE	- x
<b>Security</b> <b>Physical security</b> Kensington Lock support <b>System Security</b> Norton Internet Security Symantec <b>User Security</b> Integrated Security Panel with PIN code	x x -

User and supervisor BIOS password	x
SystemLock BIOS SmartCard security	-
Hard disk password	x
<b>Power supply</b> 1 <sup>st</sup> Li-Ion battery 6 cell 4400 mAh (48 Wh) First battery * (Mobile Mark tbd) [up to] AC adapter 20V/90W Adapter Rated voltage (AC input) 100 - 240 V Rated frequency 50 - 60 Hz DC output 20 V, 4.5 A Dynamic charge supported (rapid charge) * Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.	x 3 h  x  x
<b>Operating temperatures</b> Relative humidity (non-condensing) Ambient temperature	20% - 85% 5° - 35° C
<b>Dimensions / Weight</b> Dimensions (H x W x D) Weight* * Weight may vary depending on actual configuration	24~37 x 364 x 259 mm 2.7 kg
<b>Certificates</b> CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) CE! (Wireless) CE (Emission/Immunity) R&TTE CB Generic Report CB (Safety) RoHS WHQL TBR21	x  x x (with integrated WLAN) x x X X X X X X
<b>Operating System</b> Microsoft Windows Vista™ (XP drivers available for download) Microsoft Windows Vista® Business/ Microsoft Windows XP® Professional TwinLoad	x  x
<b>Software</b> (compatibility / preinstalled) Adobe Acrobat Reader Driver and Utility DVD (DUDVD) Easy Guide on-line user documentation Nero Norton Internet Security (incl. Firewall) 90 days Bluetooth Toshiba Stack Optional DVD Player SW	x x x x x x With Bluetooth tbd
<b>Accessories</b> (order number) AC-adapter 2 GB - 667 Case Battery 6 cell 5200 mAh (56 Wh) Memory 1GB-667 <a href="http://www.fujitsu-siemens.com/accessories/">http://www.fujitsu-siemens.com/accessories/</a>	S26391-F321-L400 S26391-F6120-L482 Value case S26391-F119-L50 S26391-F400-L400 S26391-F6120-L481

This Data Sheet describes the highest configurations. The product is offered in fixed configurations which vary from country to country and edition to edition.